

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) An open top child swing comprising:  
a frame;  
first and second hanger arms rotatably coupled to the frame; and  
a seat coupled to the first and second hanger arms, the seat having an underside to be placed on a support surface,  
wherein the frame includes a first hanger mount configured to removably receive the first hanger arm and a second hanger mount configured to removably receive the second hanger arm so that the seat can be removed from the frame,  
wherein the seat is configured to be placed on the support surface while the child remains in the seat, and  
wherein the seat maintains the same configuration when suspended from the frame and when placed on the support surface.
2. (Original) The open top child swing according to claim 1, wherein the first and second hanger arms are pivotally coupled to the seat.
3. (Currently Amended) The open top child swing according to claim 1, wherein the first and second hanger arms are movable between a hanging position, where the first and second hanger arms are positioned to engage the first and second hanger mounts, respectively, and a support position, where the first and second hanger arms are positioned to support the seat on ~~a support~~ the support surface.
4. (Original) The open top child swing according to claim 3, wherein, in the support position, each of the first and second hanger arms extends between the seat and the support surface.
5. (Original) The open top child swing according to claim 3, wherein each of the first and second hanger arms has a curved portion to contact the support surface when the first and second hanger arms are in the support position.

6. (Currently Amended) The open top child swing according to claim 1, wherein ~~an underside~~ the underside of the seat has a curved portion to enable the seat to rock when placed on ~~a support~~ the support surface.

7. (Original) The open top child swing according to claim 6, wherein the first and second hanger arms are movable between a hanging position, where the first and second hanger arms are positioned to engage the first and second hanger mounts, respectively, and an outrigger position, where the first and second hanger arms contact the support surface to prevent the seat from rocking when the seat is placed on the support surface.

8. (Original) The open top child swing according to claim 7, wherein, in the outrigger position, the first hanger arm extends outwardly from a first side of the seat and the second hanger arm extends outwardly from a second side of the seat.

9. (Original) The open top child swing according to claim 7, wherein each of the first and second hanger arms include a stop member positioned to contact the support surface when the first and second hanger arms are in the outrigger position.

10. (Original) The open top child swing according to claim 7, wherein each of the first and second hanger arms has a substantially straight portion to prevent the seat from rocking when the first and second hanger arms are in the outrigger position.

11. (Original) The open top child swing according to claim 1, wherein the first and second hanger arms are movable between a hanging position, where the first and second hanger arms are positioned to engage the first and second hanger mounts, respectively, and a carrying position, where a portion of the first hanger arm is disposed adjacent to a portion of the second hanger arm.

12. (Original) The open top child swing according to claim 11, further comprising a clasp configured to secure the first and second hanger arms in the carrying position.

13. (Original) The open top child swing according to claim 12, wherein the clasp is mounted to one of the first and second hanger arms and is configured to releasably engage the other of the first and second hanger arms.

14. (Original) The open top child swing according to claim 1, wherein the first and second hanger mounts are pivotally attached to the frame.

15. (Original) The open top child swing according to claim 1, wherein each of the first and second hanger mounts includes a rib member projecting from the hanger mount, and wherein the rib member is configured to retain the respective hanger arm on the respective hanger mount.

16. (Original) The open top child swing according to claim 15, wherein each of the first and second hanger arms includes a recess configured to slidably engage the rib member of the respective hanger arm.

17. (Original) The open top child swing according to claim 1, wherein each of the first and second hanger mounts includes a detent member projecting from the hanger mount, and wherein the detent member is configured to retain the respective hanger arm on the respective hanger mount.

18. (Original) The open top child swing according to claim 17, wherein the detent member is movable toward the hanger mount to release the respective hanger arm from the respective hanger mount.

19. (Original) The open top child swing according to claim 1, wherein each of the first and second hanger mounts includes a hook to receive the respective hanger arm.

20. (Original) The open top child swing according to claim 19, wherein the hook is substantially U-shaped to define a channel to receive the respective hanger arm.

21. (Currently Amended) A open top child swing comprising:  
a frame including  
first and second legs,  
first and second housings coupled to the first and second legs,  
respectively, and  
a battery pack to house batteries, the battery pack being removably  
mounted to one of the first and second housings; and

a seat configured to be suspended from the frame.

22. (Original) The open top child swing according to claim 21, wherein an inboard side of the housing includes a first opening and an outboard side of the housing includes a second opening.

23. (Original) The open top child swing according to claim 22, wherein the battery pack includes a first flex member engageable with the first opening and a second flex member engageable with the second opening to retain the battery pack in the housing.

24. (Original) The open top child swing according to claim 23, wherein the flex members disengage from the openings when pressed toward the openings.

25. (Currently Amended) A child swing comprising:  
frame components including first and second legs, first and second housings coupled to the first and second legs, respectively, and first and second hanger mounts coupled to the first and second housings, respectively; and

a seat assembly suspended from the frame components, the seat assembly including first and second hanger arms removably coupled to the first and second hanger mounts, respectively, and a seat coupled to the first and second hanger arms,

wherein, when the seat assembly is removed from the first and second hanger mounts, an area between the first frame components and the second frame components is open,

wherein the seat has an underside to be placed on a support surface and is configured to be placed on the support surface while the child remains in the seat, and

wherein the seat maintains the same configuration when suspended from the frame components and when placed on the support surface.

26. (New) An open top child swing comprising:  
a frame;  
a seat suspended from the frame by at least one hanger arm to swing relative to the frame, the seat and the at least one hanger arm being removable from the frame; and  
a motor mechanism to drive the swinging motion of the seat,

wherein the seat has an underside to be placed on a support surface and is configured to be placed on the support surface while the child remains in the seat, and

wherein the seat maintains the same configuration when suspended from the frame and when placed on the surface.

27. (New) The open top swing according to claim 26, wherein the at least one hanger arm comprises first and second hanger arms.